

QUALITY PACKAGED CONCRETE PRODUCTS NATIONWIDE



**Description:**

**PAKMIX® Portland Cement type I & II** provides the basic performance characteristics of Type I portland cement, as well as the moderate sulfate resistance and lower heat of hydration characteristic of Type II portland cement. PAKMIX® Portland Cement type I & II is an exceptionally versatile basic building material, suitable for a variety of concrete construction applications. Meets the ASTM C 150 in the Standard Specification for Portland Cement.



Mixing Ratio for Concrete

Cement .....	1
Part .....	
Sand .....	2
Parts .....	
Gravel .....	3
Parts .....	

Mixing Ratio for Mortar

Cement .....	1
Part .....	
Lime .....	1/2
Parts .....	
Sand .....	3 1/2 to 4 1/2
Parts .....	

CALIFORNIA PROPOSITION 65 WARNING

This product contains crystalline silica (CAS #14808-60-7) which is "known to the State of California to cause cancer and other substances which are known to the State of California to cause cancer, birth defects and reproductive harm."

Avoid contact with Skin – Injurious to eyes  
Contains Portland cement, freshly mixed cement, mortar, concrete or grout may cause skin injury. If exposed, wash skin promptly and repeatedly for 15 minutes. The use of gloves and protective eyewear is recommended. If any cement or cement mixtures get into the eyes, rinse immediately and repeatedly with water for 15 minutes and get prompt medical attention.

**Keep Out of Reach of Children:**  
Material safety data sheet available upon request.

PORTLAND CEMENT I & II

PRO LINE



605 Industrial Way, Dixon, California 95620  
(800) 272-5649 • FAX (707) 693-9349  
www.pakmix.com

PORTLAND CEMENT TYPE I & II